

UMBRELLA BASE GUIDE **BY APPLICATION**

- **TABLE USE:** Indicates the base is suitable for use beneath a table. It is not recommended as a free-standing base option.
- **FREE-STANDING:** Indicates the base is recommended as a free-standing option, but also suitable for use beneath a table if the table provides enough clearance to safely sit above the base on a flat surface. 18" (18ST/2) Stems should always be used when in this application.
- **1.5"/38mm STEM:** Indicates the base can accommodate an 1.5"/38mm center pole.
- **2"/50mm STEM:** Indicates the base can accommodate a 2"/50mm (18ST2) center pole.

| | 7.5' OCT. / 2.3m | 9' OCT. / 2.7m | 11' OCT. / 3.5m | 13' OCT. / 4m | 6.5' SQ. / 2m | 7.5' SQ. / 2.3m | 10' SQ. / 3m | 8' X 10' REC. / 3m | 8.5' X 11' REC. / 3.5m |
|--------------------------|------------------|----------------|-----------------|---------------|---------------|-----------------|--------------|--------------------|------------------------|
| ALUMINUM SHELL | | | | | | | | | |
| 502A | ● ● | | | | ● ● | | | | |
| RESIN COATED | | | | | | | | | |
| 50C | ● ● | ● ● | ● ● | | ● ● | ● ● | | ● ● | |
| 23 | ● ● | ● ● | ● ● | | ● ● | ● ● | | ● ● | |
| ALUMINUM CONCRETE | | | | | | | | | |
| 100A | ● ● ● | ● ● ● | ● ● ● | | ● ● ● | ● ● | | ● ● | |
| 150A | ● ● ● | ● ● ● | ● ● ● | ● ● | ● ● ● | ● ● ● | ● ● | ● ● ● | ● ● |
| STEEL PLATE | | | | | | | | | |
| 50S | ● ● | ● ● | ● ● | | ● ● | ● ● | | ● ● | |
| 75S | ● ● | ● ● | ● ● | | ● ● | ● ● | | | |
| GALVANIZED STEEL | | | | | | | | | |
| 24G | ● ● ● | ● ● ● | ● ● | | ● ● ● | ● ● | | ● ● | |
| 30G | ● ● ● | ● ● ● | ● ● ● | | ● ● ● | ● ● ● | | ● ● ● | |
| 36G | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● |
| 40G | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● |
| 20G-SQ | ● ● ● | ● ● | ● ● | | ● ● | ● ● | | ● ● | |
| 24G-SQ | ● ● ● | ● ● ● | ● ● ● | | ● ● ● | ● ● ● | | ● ● | |
| 36G-SQ | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● |
| WHEEL BASE | | | | | | | | | |
| ARU/ECU-480 | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● | ● ● |

NOTE: 18" stems (18ST/2) are recommended for free-standing applications. Frankford will not recommend a free-standing application with a shorter stem. The 75S (16" stem) is considered a free-standing base as noted above.